US 20230009245A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2023/0009245 A1**

Moeykens (43) **Pub. Date: Jan. 12, 2023**

(54) **ELECTRIC AIRCRAFT CONFIGURED TO IMPLEMENT A LAYERED DATA NETWORK AND METHOD TO IMPLEMENT A LAYERED DATA NETWORK IN ELECTRIC AIRCRAFT**

(71) Applicant: **BETA AIR, LLC**, SOUTH BURLINGTON, VT (US)

(72) Inventor: **Vincent Moeykens**, BURLINGTON, VT (US)

(73) Assignee: **BETA AIR, LLC**, SOUTH BURLINGTON, VT (US)

(21) Appl. No.: **17/678,463**

(22) Filed: **Feb. 23, 2022**

Related U.S. Application Data

(63) Continuation of application No. 17/373,438, filed on Jul. 12, 2021, now Pat. No. 11,276,315.

Publication Classification

(51) **Int. Cl.**

G08G 5/00	(2006.01)
B64D 41/00	(2006.01)
G05D 1/06	(2006.01)

(52) **U.S. Cl.**

CPC ***G08G 5/0008*** (2013.01); ***B64D 41/00*** (2013.01); ***G05D 1/0669*** (2013.01); ***G08G 5/0021*** (2013.01)

(57) **ABSTRACT**

An electric aircraft configured to implement a layered data network is provided. The electric aircraft generally includes a first communication component, a second communication component and a third communication component. The first communication component is configured to communicate with a first layer providing radio communication between the electric aircraft and at least a first party at a first bandwidth. The second communication component is configured to communicate with a second layer providing mobile network communication between the electric aircraft and at least a second party at a second bandwidth. The third communication component is configured to communicate with a third layer providing satellite communication between the electric aircraft and at least a third party at a third bandwidth. A method to implement a layered data network in an electric aircraft is also provided.





FIG. 1


200
Radio Tower
Mobile Network Tower
Satellite
AIRCRAFT
Flight Controller
Energy Source
Flight Component
First Communication Component 204
Antenna 240
Second Communication Component 216
Third Communication Component 228
First Layer 208
Second Layer 220
Third Layer 232
First Party 212
Second Party 224
Third Party 236

FIG. 2


300
Pilot Signal 336
Flight Controller 304
Signal Transformation Component 308
Intermediate Representation 312
Reconfigurable Platform 316
Logic Component 320
Sub-Controller 340
Flight Element 324
Chipset Component 328
Co-Controller 344
Flight Component 108

FIG. 3


Input
412
Output
408
Machine-Learning Module
400
Machine-Learning
Model
424
Unsupervised
Machine-Learning
Process
432
Lazy Learning
Process
420
Supervised
Machine-Learning
Process
428
Training Data
404
Training Data Classifier
416

FIG. 4


500
Communicating with a First Layer Providing Radio Communication Between an Aircraft and at Least a First Party at a First Bandwidth
504
Communicating with a Second Layer Providing Mobile Network Communication Between the Aircraft and at Least a Second Party at a Second Bandwidth
508
Communicating with a Third Layer Providing Satellite Communication Between the Aircraft and at Least a Third Party at a Third Bandwidth
512

FIG. 5


600
Display
636
624
Storage Device
628
Medium
620
Instructions
652
632
Display Adaptor
Input Device
612
616
Instructions
Processor(s)
Peripheral Interface(s)
Input/ Output System
Instructions
Memory
Network Interface
640
604
620
656
608
620
Remote Device
648
Network
644

FIG. 6

ELECTRIC AIRCRAFT CONFIGURED TO IMPLEMENT A LAYERED DATA NETWORK AND METHOD TO IMPLEMENT A LAYERED DATA NETWORK IN ELECTRIC AIRCRAFT

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is a continuation of Non-provisional application Ser. No. 17/373,438 filed on Jul. 12, 2021 and entitled "AN ELECTRIC AIRCRAFT CONFIGURED TO IMPLEMENT A LAYERED DATA NETWORK AND METHOD TO IMPLEMENT A LAYERED DATA NETWORK IN ELECTRIC AIRCRAFT," the entirety of which is incorporated herein by reference.

FIELD OF THE INVENTION

[0002] The present invention generally relates to the field of data communication for electric aircraft. In particular, the present invention is directed to an electric aircraft configured to implement a layered data network and method to implement a layered data network in electric aircraft.

BACKGROUND

[0003] It is important to maintain reliable communication between an aircraft and other related entities. Many systems which provide data communication from and to an electric aircraft are unable to adequately handle this task.

SUMMARY OF THE DISCLOSURE

[0004] In an aspect an electric aircraft configured to implement a layered data network is provided. The electric aircraft generally includes a first communication component, a second communication component and a third communication component. The first communication component is configured to communicate with a first layer providing radio communication between the electric aircraft and at least a first party at a first bandwidth. The second communication component is configured to communicate with a second layer providing mobile network communication between the electric aircraft and at least a second party at a second bandwidth. The third communication component is configured to communicate with a third layer providing satellite communication between the electric aircraft and at least a third party at a third bandwidth.

[0005] In another aspect a method to implement a layered data network in electric aircraft is provided. The method includes communicating, by a first communication component of an electric aircraft, with a first layer which provides radio communication between the electric aircraft and at least a first party at a first bandwidth, communicating, by a second communication component of the electric aircraft, with a second layer which provides mobile network communication between the electric aircraft and at least a second party at a second bandwidth, and communicating, by a third communication component of the electric aircraft, with a third layer which provides satellite communication between the electric aircraft and at least a third party at a third bandwidth.

[0006] These and other aspects and features of non-limiting embodiments of the present invention will become apparent to those skilled in the art upon review of the following description of specific non-limiting embodiments of the invention in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] For the purpose of illustrating the invention, the drawings show aspects of one or more embodiments of the invention. However, it should be understood that the present invention is not limited to the precise arrangements and instrumentalities shown in the drawings, wherein:

[0008] FIG. **1** is a diagrammatic representation of an exemplary embodiment of an electric aircraft;

[0009] FIG. **2** is a block diagram illustrating an exemplary embodiment of an electric aircraft configured to implement a layered data network;

[0010] FIG. **3** is a block diagram illustrating an exemplary embodiment of a flight controller;

[0011] FIG. **4** is a block diagram of an exemplary embodiment of a machine-learning module;

[0012] FIG. **5** is a block diagram illustrating an exemplary embodiment of a method to implement a layered data network in an electric aircraft; and

[0013] FIG. **6** is a block diagram of a computing system that can be used to implement any one or more of the methodologies disclosed herein and any one or more portions thereof.

[0014] The drawings are not necessarily to scale and may be illustrated by phantom lines, diagrammatic representations and fragmentary views. In certain instances, details that are not necessary for an understanding of the embodiments or that render other details difficult to perceive may have been omitted.

DETAILED DESCRIPTION

[0015] In the following description, for the purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of the present invention. It will be apparent, however, that the present invention may be practiced without these specific details. As used herein, the word "exemplary" or "illustrative" means "serving as an example, instance, or illustration." Any implementation described herein as "exemplary" or "illustrative" is not necessarily to be construed as preferred or advantageous over other implementations. All of the implementations described below are exemplary implementations provided to enable persons skilled in the art to make or use the embodiments of the disclosure and are not intended to limit the scope of the disclosure, which is defined by the claims. For purposes of description herein, the terms "upper", "lower", "left", "rear", "right", "front", "vertical", "horizontal", "upward", "downward", "forward", "backward" and derivatives thereof shall relate to the invention as oriented in FIG. **1**. Furthermore, there is no intention to be bound by any expressed or implied theory presented in the preceding technical field, background, brief summary or the following detailed description. It is also to be understood that the specific devices and processes illustrated in the attached drawings, and described in the following specification, are simply exemplary embodiments of the inventive concepts defined in the appended claims. Hence, specific dimensions and other physical characteristics relating to the embodiments disclosed herein are not to be considered as limiting, unless the claims expressly state otherwise.

[0016] At a high level, aspects of the present disclosure are directed to systems and methods for data communication by implementation of a layered data network. In an embodiment, an electric aircraft configured to implement a layered data network is provided. Aspects of the present disclosure can be used in a method to implement a layered data network in an electric aircraft. Advantageously, aspects of the present disclosure allow for reliable communication between an aircraft, such as an electric aircraft, and other parties, for example, and without limitation, other aircraft, recharging stations, air traffic control towers, and the like. Exemplary embodiments illustrating aspects of the present disclosure are described below in the context of several specific examples.

[0017] Referring now to FIG. **1**, an exemplary embodiment of an aircraft **100**, which may include an electric aircraft, and which is configured to implement a layered data network, is illustrated. As used in this disclosure an "aircraft" is any vehicle that may fly by gaining support from the air. As a non-limiting example, aircraft may include airplanes, helicopters, commercial and/or recreational aircrafts, instrument flight aircrafts, drones, electric aircrafts, airliners, rotorcrafts, vertical takeoff and landing aircrafts, jets, airships, blimps, gliders, paramotors, and the like thereof. Aircraft **100** may include an electrically powered aircraft. In embodiments, electrically powered aircraft may be an electric vertical takeoff and landing (eVTOL) aircraft. Electric aircraft may be capable of rotor-based cruising flight, rotor-based takeoff, rotor-based landing, fixed-wing cruising flight, airplane-style takeoff, airplane-style landing, and/or any combination thereof. Electric aircraft may include one or more manned and/or unmanned aircrafts. Electric aircraft may include one or more all-electric short takeoff and landing (eSTOL) aircrafts. For example, and without limitation, eSTOL aircrafts may accelerate the plane to a flight speed on takeoff and decelerate the plane after landing. In an embodiment, and without limitation, electric aircraft may be configured with an electric propulsion assembly. Electric propulsion assembly may include any electric propulsion assembly as described in U.S. Nonprovisional application Ser. No. 16/703,225, filed on Dec. 4, 2019, and entitled "AN INTEGRATED ELECTRIC PROPULSION ASSEMBLY," the entirety of which is incorporated herein by reference.

[0018] Still referring to FIG. **1**, aircraft **100** includes a fuselage **104**. As used in this disclosure a "fuselage" is the main body of an aircraft, or in other words, the entirety of the aircraft except for the cockpit, nose, wings, empennage, nacelles, any and all control surfaces, and generally contains an aircraft's payload. Fuselage **104** may include structural elements that physically support a shape and structure of an aircraft. Structural elements may take a plurality of forms, alone or in combination with other types. Structural elements may vary depending on a construction type of aircraft such as without limitation a fuselage **104**. Fuselage **104** may comprise a truss structure. A truss structure may be used with a lightweight aircraft and comprises welded steel tube trusses. A "truss," as used in this disclosure, is an assembly of beams that create a rigid structure, often in combinations of triangles to create three-dimensional shapes. A truss structure may alternatively comprise wood construction in place of steel tubes, or a combination thereof. In embodiments, structural elements may comprise steel tubes and/or wood beams. In an embodiment, and without limitation, structural elements may include an aircraft skin. Aircraft skin may be layered over the body shape constructed by trusses. Aircraft skin may comprise a plurality of materials such as plywood sheets, aluminum, fiberglass, and/or carbon fiber, the latter of which will be addressed in greater detail later herein.

[0019] In embodiments, and with continued reference to FIG. **1**, aircraft fuselage **104** may include and/or be constructed using geodesic construction. Geodesic structural elements may include stringers wound about formers (which may be alternatively called station frames) in opposing spiral directions. A "stringer," as used in this disclosure, is a general structural element that includes a long, thin, and rigid strip of metal or wood that is mechanically coupled to and spans a distance from, station frame to station frame to create an internal skeleton on which to mechanically couple aircraft skin. A former (or station frame) may include a rigid structural element that is disposed along a length of an interior of aircraft fuselage **104** orthogonal to a longitudinal (nose to tail) axis of the aircraft and may form a general shape of fuselage **104**. A former may include differing cross-sectional shapes at differing locations along fuselage **104**, as the former is the structural element that informs the overall shape of a fuselage **104** curvature. In embodiments, aircraft skin may be anchored to formers and strings such that the outer mold line of a volume encapsulated by formers and stringers comprises the same shape as aircraft **100** when installed. In other words, former(s) may form a fuselage's ribs, and the stringers may form the interstitials between such ribs. The spiral orientation of stringers about formers may provide uniform robustness at any point on an aircraft fuselage such that if a portion sustains damage, another portion may remain largely unaffected. Aircraft skin may be mechanically coupled to underlying stringers and formers and may interact with a fluid, such as air, to generate lift and perform maneuvers.

[0020] In an embodiment, and still referring to FIG. **1**, fuselage **104** may include and/or be constructed using monocoque construction. Monocoque construction may include a primary structure that forms a shell (or skin in an aircraft's case) and supports physical loads. Monocoque fuselages are fuselages in which the aircraft skin or shell is also the primary structure. In monocoque construction aircraft skin would support tensile and compressive loads within itself and true monocoque aircraft can be further characterized by the absence of internal structural elements. Aircraft skin in this construction method is rigid and can sustain its shape with no structural assistance form underlying skeleton-like elements. Monocoque fuselage may comprise aircraft skin made from plywood layered in varying grain directions, epoxy-impregnated fiberglass, carbon fiber, or any combination thereof.

[0021] According to embodiments, and further referring to FIG. **1**, fuselage **104** may include a semi-monocoque construction. Semi-monocoque construction, as used herein, is a partial monocoque construction, wherein a monocoque construction is describe above detail. In semi-monocoque construction, aircraft fuselage **104** may derive some structural support from stressed aircraft skin and some structural support from underlying frame structure made of structural elements. Formers or station frames can be seen running transverse to the long axis of fuselage **104** with circular cutouts which are generally used in real-world manufacturing for weight savings and for the routing of electrical harnesses and other modern on-board systems. In a semi-

monocoque construction, stringers are thin, long strips of material that run parallel to fuselage's long axis. Stringers may be mechanically coupled to formers permanently, such as with rivets. Aircraft skin may be mechanically coupled to stringers and formers permanently, such as by rivets as well. A person of ordinary skill in the art will appreciate, upon reviewing the entirety of this disclosure, that there are numerous methods for mechanical fastening of the aforementioned components like screws, nails, dowels, pins, anchors, adhesives like glue or epoxy, or bolts and nuts, to name a few. A subset of fuselage under the umbrella of semi-monocoque construction includes unibody vehicles. Unibody, which is short for "unitized body" or alternatively "unitary construction", vehicles are characterized by a construction in which the body, floor plan, and chassis form a single structure. In the aircraft world, unibody may be characterized by internal structural elements like formers and stringers being constructed in one piece, integral to the aircraft skin as well as any floor construction like a deck.

[0022] Still referring to FIG. **1**, stringers and formers, which may account for the bulk of an aircraft structure excluding monocoque construction, may be arranged in a plurality of orientations depending on aircraft operation and materials. Stringers may be arranged to carry axial (tensile or compressive), shear, bending or torsion forces throughout their overall structure. Due to their coupling to aircraft skin, aerodynamic forces exerted on aircraft skin will be transferred to stringers. A location of said stringers greatly informs the type of forces and loads applied to each and every stringer, all of which may be handled by material selection, cross-sectional area, and mechanical coupling methods of each member. A similar assessment may be made for formers. In general, formers may be significantly larger in cross-sectional area and thickness, depending on location, than stringers. Both stringers and formers may comprise aluminum, aluminum alloys, graphite epoxy composite, steel alloys, titanium, or an undisclosed material alone or in combination.

[0023] In an embodiment, and still referring to FIG. **1**, stressed skin, when used in semi-monocoque construction is the concept where the skin of an aircraft bears partial, yet significant, load in an overall structural hierarchy. In other words, an internal structure, whether it be a frame of welded tubes, formers and stringers, or some combination, may not be sufficiently strong enough by design to bear all loads. The concept of stressed skin may be applied in monocoque and semi-monocoque construction methods of fuselage **104**. Monocoque comprises only structural skin, and in that sense, aircraft skin undergoes stress by applied aerodynamic fluids imparted by the fluid. Stress as used in continuum mechanics may be described in pound-force per square inch (lbf/in^2) or Pascals (Pa). In semi-monocoque construction stressed skin may bear part of aerodynamic loads and additionally may impart force on an underlying structure of stringers and formers.

[0024] Still referring to FIG. **1**, it should be noted that an illustrative embodiment is presented only, and this disclosure in no way limits the form or construction method of a system and method for loading payload into an eVTOL aircraft. In embodiments, fuselage **104** may be configurable based on the needs of the eVTOL per specific mission or objective. The general arrangement of components, structural elements, and hardware associated with storing and/or moving a payload may be added or removed from fuselage **104** as needed, whether it is stowed manually, automatedly, or removed by personnel altogether. Fuselage **104** may be configurable for a plurality of storage options. Bulkheads and dividers may be installed and uninstalled as needed, as well as longitudinal dividers where necessary. Bulkheads and dividers may be installed using integrated slots and hooks, tabs, boss and channel, or hardware like bolts, nuts, screws, nails, clips, pins, and/or dowels, to name a few. Fuselage **104** may also be configurable to accept certain specific cargo containers, or a receptable that can, in turn, accept certain cargo containers.

[0025] Still referring to FIG. **1**, aircraft **100** may include a plurality of laterally extending elements attached to fuselage **104**. As used in this disclosure a "laterally extending element" is an element that projects essentially horizontally from fuselage, including an outrigger, a spar, and/or a fixed wing that extends from fuselage. Wings may be structures which include airfoils configured to create a pressure differential resulting in lift. Wings may generally dispose on the left and right sides of the aircraft symmetrically, at a point between nose and empennage. Wings may comprise a plurality of geometries in planform view, swept swing, tapered, variable wing, triangular, oblong, elliptical, square, among others. A wing's cross section geometry may comprise an airfoil. An "airfoil" as used in this disclosure is a shape specifically designed such that a fluid flowing above and below it exert differing levels of pressure against the top and bottom surface. In embodiments, the bottom surface of an aircraft can be configured to generate a greater pressure than does the top, resulting in lift. Laterally extending element may comprise differing and/or similar cross-sectional geometries over its cord length or the length from wing tip to where wing meets the aircraft's body. One or more wings may be symmetrical about the aircraft's longitudinal plane, which comprises the longitudinal or roll axis reaching down the center of the aircraft through the nose and empennage, and the plane's yaw axis. Laterally extending element may comprise controls surfaces configured to be commanded by a pilot or pilots to change a wing's geometry and therefore its interaction with a fluid medium, like air. Control surfaces may comprise flaps, ailerons, tabs, spoilers, and slats, among others. The control surfaces may dispose on the wings in a plurality of locations and arrangements and in embodiments may be disposed at the leading and trailing edges of the wings, and may be configured to deflect up, down, forward, aft, or a combination thereof. An aircraft, including a dual-mode aircraft may comprise a combination of control surfaces to perform maneuvers while flying or on ground.

[0026] Still referring to FIG. **1**, aircraft **100** includes a plurality of flight components **108**. As used in this disclosure a "flight component" is a component that promotes flight and guidance of an aircraft. In an embodiment, flight component **108** may be mechanically coupled to an aircraft. As used herein, a person of ordinary skill in the art would understand "mechanically coupled" to mean that at least a portion of a device, component, or circuit is connected to at least a portion of the aircraft via a mechanical coupling. Said mechanical coupling can include, for example, rigid coupling, such as beam coupling, bellows coupling, bushed pin coupling, constant velocity, split-muff coupling, diaphragm coupling, disc coupling, donut coupling, elastic coupling, flexible coupling, fluid coupling, gear coupling, grid coupling, hirth joints, hydrodynamic coupling, jaw coupling,

magnetic coupling, Oldham coupling, sleeve coupling, tapered shaft lock, twin spring coupling, rag joint coupling, universal joints, or any combination thereof. In an embodiment, mechanical coupling may be used to connect the ends of adjacent parts and/or objects of an electric aircraft. Further, in an embodiment, mechanical coupling may be used to join two pieces of rotating electric aircraft components.

[0027] Still referring to FIG. **1**, plurality of flight components **108** may include at least a lift propulsor component **112**. As used in this disclosure a "lift propulsor component" is a component and/or device used to propel a craft upward by exerting downward force on a fluid medium, which may include a gaseous medium such as air or a liquid medium such as water. Lift propulsor component **112** may include any device or component that consumes electrical power on demand to propel an electric aircraft in a direction or other vehicle while on ground or in-flight. For example, and without limitation, lift propulsor component **112** may include a rotor, propeller, paddle wheel and the like thereof, wherein a rotor is a component that produces torque along the longitudinal axis, and a propeller produces torquer along the vertical axis. In an embodiment, lift propulsor component **112** includes a plurality of blades. As used in this disclosure a "blade" is a propeller that converts rotary motion from an engine or other power source into a swirling slipstream. In an embodiment, blade may convert rotary motion to push the propeller forwards or backwards. In an embodiment lift propulsor component **112** may include a rotating power-driven hub, to which are attached several radial airfoil-section blades such that the whole assembly rotates about a longitudinal axis. Blades may be configured at an angle of attack, wherein an angle of attack is described in detail below. In an embodiment, and without limitation, angle of attack may include a fixed angle of attack. As used in this disclosure a "fixed angle of attack" is fixed angle between a chord line of a blade and relative wind. As used in this disclosure a "fixed angle" is an angle that is secured and/or unmovable from the attachment point. For example, and without limitation fixed angle of attack may be 3.2° as a function of a pitch angle of 9.7° and a relative wind angle 6.5°. In another embodiment, and without limitation, angle of attack may include a variable angle of attack. As used in this disclosure a "variable angle of attack" is a variable and/or moveable angle between a chord line of a blade and relative wind. As used in this disclosure a "variable angle" is an angle that is moveable from an attachment point. For example, and without limitation variable angle of attack may be a first angle of 4.7° as a function of a pitch angle of 7.1° and a relative wind angle 2.4°, wherein the angle adjusts and/or shifts to a second angle of 2.7° as a function of a pitch angle of 5.1° and a relative wind angle 2.4°. In an embodiment, angle of attack be configured to produce a fixed pitch angle. As used in this disclosure a "fixed pitch angle" is a fixed angle between a cord line of a blade and the rotational velocity direction. For example, and without limitation, fixed pitch angle may include 18°. In another embodiment fixed angle of attack may be manually variable to a few set positions to adjust one or more lifts of the aircraft prior to flight. In an embodiment, blades for an aircraft are designed to be fixed to their hub at an angle similar to the thread on a screw makes an angle to the shaft; this angle may be referred to as a pitch or pitch angle which will determine a speed of forward movement as the blade rotates.

[0028] In an embodiment, and still referring to FIG. **1**, lift propulsor component **112** may be configured to produce a lift. As used in this disclosure a "lift" is a perpendicular force to the oncoming flow direction of fluid surrounding the surface. For example, and without limitation relative air speed may be horizontal to aircraft **100**, wherein lift force may be a force exerted in a vertical direction, directing aircraft **100** upwards. In an embodiment, and without limitation, lift propulsor component **112** may produce lift as a function of applying a torque to lift propulsor component. As used in this disclosure a "torque" is a measure of force that causes an object to rotate about an axis in a direction. For example, and without limitation, torque may rotate an aileron and/or rudder to generate a force that may adjust and/or affect altitude, airspeed velocity, groundspeed velocity, direction during flight, and/or thrust. For example, one or more flight components **108** such as a power sources may apply a torque on lift propulsor component **112** to produce lift. As used in this disclosure a "power source" is a source that that drives and/or controls any other flight component. For example, and without limitation power source may include a motor that operates to move one or more lift propulsor components, to drive one or more blades, or the like thereof. A motor may be driven by direct current (DC) electric power and may include, without limitation, brushless DC electric motors, switched reluctance motors, induction motors, or any combination thereof. A motor may also include electronic speed controllers or other components for regulating motor speed, rotation direction, and/or dynamic braking.

[0029] Still referring to FIG. **1**, power source may include an energy source. An energy source may include, for example, an electrical energy source a generator, a photovoltaic device, a fuel cell such as a hydrogen fuel cell, direct methanol fuel cell, and/or solid oxide fuel cell, an electric energy storage device (e.g., a capacitor, an inductor, and/or a battery). An electrical energy source may also include a battery cell, or a plurality of battery cells connected in series into a module and each module connected in series or in parallel with other modules. Configuration of an energy source containing connected modules may be designed to meet an energy or power requirement and may be designed to fit within a designated footprint in an electric aircraft in which aircraft **100** may be incorporated.

[0030] In an embodiment, and still referring to FIG. **1**, an energy source may be used to provide a steady supply of electrical power to a load over the course of a flight by a vehicle or other electric aircraft. For example, an energy source may be capable of providing sufficient power for "cruising" and other relatively low-energy phases of flight. An energy source may also be capable of providing electrical power for some higher-power phases of flight as well, particularly when the energy source is at a high SOC, as may be the case for instance during takeoff. In an embodiment, an energy source may be capable of providing sufficient electrical power for auxiliary loads including without limitation, lighting, navigation, communications, de-icing, steering or other systems requiring power or energy. Further, an energy source may be capable of providing sufficient power for controlled descent and landing protocols, including, without limitation, hovering descent or runway landing. As used herein an energy source may have high power density where electrical power an energy source can usefully produce per unit of volume and/or mass is relatively high. "Electrical

power," as used in this disclosure, is defined as a rate of electrical energy per unit time. An energy source may include a device for which power that may be produced per unit of volume and/or mass has been optimized, at the expense of the maximal total specific energy density or power capacity, during design. Non-limiting examples of items that may be used as at least an energy source may include batteries used for starting applications including Li ion batteries which may include NCA, NMC, Lithium iron phosphate (LiFePO4) and Lithium Manganese Oxide (LMO) batteries, which may be mixed with another cathode chemistry to provide more specific power if the application requires Li metal batteries, which have a lithium metal anode that provides high power on demand, Li ion batteries that have a silicon or titanite anode, energy source may be used, in an embodiment, to provide electrical power to an electric aircraft or drone, such as an electric aircraft vehicle, during moments requiring high rates of power output, including without limitation takeoff, landing, thermal deicing and situations requiring greater power output for reasons of stability, such as high turbulence situations, as described in further detail below. A battery may include, without limitation a battery using nickel based chemistries such as nickel cadmium or nickel metal hydride, a battery using lithium ion battery chemistries such as a nickel cobalt aluminum (NCA), nickel manganese cobalt (NMC), lithium iron phosphate (LiFePO4), lithium cobalt oxide (LCO), and/or lithium manganese oxide (LMO), a battery using lithium polymer technology, lead-based batteries such as without limitation lead acid batteries, metal-air batteries, or any other suitable battery. Persons skilled in the art, upon reviewing the entirety of this disclosure, will be aware of various devices of components that may be used as an energy source.

[0031] Still referring to FIG. **1**, an energy source may include a plurality of energy sources, referred to herein as a module of energy sources. A module may include batteries connected in parallel or in series or a plurality of modules connected either in series or in parallel designed to deliver both the power and energy requirements of the application. Connecting batteries in series may increase the voltage of at least an energy source which may provide more power on demand. High voltage batteries may require cell matching when high peak load is needed. As more cells are connected in strings, there may exist the possibility of one cell failing which may increase resistance in the module and reduce an overall power output as a voltage of the module may decrease as a result of that failing cell. Connecting batteries in parallel may increase total current capacity by decreasing total resistance, and it also may increase overall amp-hour capacity. Overall energy and power outputs of at least an energy source may be based on individual battery cell performance or an extrapolation based on measurement of at least an electrical parameter. In an embodiment where an energy source includes a plurality of battery cells, overall power output capacity may be dependent on electrical parameters of each individual cell. If one cell experiences high self-discharge during demand, power drawn from at least an energy source may be decreased to avoid damage to the weakest cell. An energy source may further include, without limitation, wiring, conduit, housing, cooling system and battery management system. Persons skilled in the art will be aware, after reviewing the entirety of this disclosure, of many different components of an energy source.

[0032] In an embodiment and still referring to FIG. **1**, plurality of flight components **108** may be arranged in a quad copter orientation. As used in this disclosure a "quad copter orientation" is at least a lift propulsor component oriented in a geometric shape and/or pattern, wherein each of the lift propulsor components are located along a vertex of the geometric shape. For example, and without limitation, a square quad copter orientation may have four lift propulsor components oriented in the geometric shape of a square, wherein each of the four lift propulsor components are located along the four vertices of the square shape. As a further non-limiting example, a hexagonal quad copter orientation may have six lift propulsor components oriented in the geometric shape of a hexagon, wherein each of the six lift propulsor components are located along the six vertices of the hexagon shape. In an embodiment, and without limitation, quad copter orientation may include a first set of lift propulsor components and a second set of lift propulsor components, wherein the first set of lift propulsor components and the second set of lift propulsor components may include two lift propulsor components each, wherein the first set of lift propulsor components and a second set of lift propulsor components are distinct from one another. For example, and without limitation, the first set of lift propulsor components may include two lift propulsor components that rotate in a clockwise direction, wherein the second set of lift propulsor components may include two lift propulsor components that rotate in a counterclockwise direction. In an embodiment, and without limitation, the first set of propulsor lift components may be oriented along a line oriented 45° from the longitudinal axis of aircraft **100**. In another embodiment, and without limitation, the second set of propulsor lift components may be oriented along a line oriented 135° from the longitudinal axis, wherein the first set of lift propulsor components line and the second set of lift propulsor components are perpendicular to each other.

[0033] Still referring to FIG. **1**, plurality of flight components **108** may include a pusher component **116**. As used in this disclosure a "pusher component" is a component that pushes and/or thrusts an aircraft through a medium. As a non-limiting example, pusher component **116** may include a pusher propeller, a paddle wheel, a pusher motor, a pusher propulsor, and the like. Additionally, or alternatively, pusher flight component may include a plurality of pusher flight components. Pusher component **116** is configured to produce a forward thrust. As used in this disclosure a "forward thrust" is a thrust that forces aircraft through a medium in a horizontal direction, wherein a horizontal direction is a direction parallel to the longitudinal axis. As a non-limiting example, forward thrust may include a force of 1145 N to force aircraft to in a horizontal direction along the longitudinal axis. As a further non-limiting example, forward thrust may include a force of, as a non-limiting example, 300 N to force aircraft **100** in a horizontal direction along a longitudinal axis. As a further non-limiting example, pusher component **116** may twist and/or rotate to pull air behind it and, at the same time, push aircraft **100** forward with an equal amount of force. In an embodiment, and without limitation, the more air forced behind aircraft, the greater the thrust force with which the aircraft is pushed horizontally will be. In another embodiment, and without limitation, forward thrust may force aircraft **100** through the medium of relative air. Additionally or alternatively, plurality of flight components **108** may include one or more puller components. As

used in this disclosure a "puller component" is a component that pulls and/or tows an aircraft through a medium. As a non-limiting example, puller component may include a flight component such as a puller propeller, a puller motor, a tractor propeller, a puller propulsor, and the like. Additionally, or alternatively, puller component may include a plurality of puller flight components.

[0034] In an embodiment and still referring to FIG. **1**, aircraft **100** may include a flight controller located within fuselage **104**, wherein a flight controller is described in detail below, in reference to FIG. **3**. In an embodiment, and without limitation, flight controller may be configured to operate a fixed-wing flight capability. As used in this disclosure a "fixed-wing flight capability" is a method of flight wherein the plurality of laterally extending elements generate lift. For example, and without limitation, fixed-wing flight capability may generate lift as a function of an airspeed of aircraft **100** and one or more airfoil shapes of the laterally extending elements, wherein an airfoil is described above in detail. As a further non-limiting example, flight controller may operate the fixed-wing flight capability as a function of reducing applied torque on lift propulsor component **112**. For example, and without limitation, flight controller may reduce a torque of 9 Nm applied to a first set of lift propulsor components to a torque of 2 Nm. As a further non-limiting example, flight controller may reduce a torque of 12 Nm applied to a first set of lift propulsor components to a torque of 0 Nm. In an embodiment, and without limitation, flight controller may produce fixed-wing flight capability as a function of increasing forward thrust exerted by pusher component **116**. For example, and without limitation, flight controller may increase a forward thrust of 100 kN produced by pusher component **116** to a forward thrust of 569 kN. In an embodiment, and without limitation, an amount of lift generation may be related to an amount of forward thrust generated to increase airspeed velocity, wherein the amount of lift generation may be directly proportional to the amount of forward thrust produced. Additionally or alternatively, flight controller may include an inertia compensator. As used in this disclosure an "inertia compensator" is one or more computing devices, electrical components, logic circuits, processors, and the like there of that are configured to compensate for inertia in one or more lift propulsor components present in aircraft **100**. Inertia compensator may alternatively or additionally include any computing device used as an inertia compensator as described in U.S. Nonprovisional application Ser. No. 17/106,557, filed on Nov. 30, 2020, and entitled "SYSTEM AND METHOD FOR FLIGHT CONTROL IN ELECTRIC AIRCRAFT," the entirety of which is incorporated herein by reference.

[0035] In an embodiment, and still referring to FIG. **1**, flight controller may be configured to perform a reverse thrust command. As used in this disclosure a "reverse thrust command" is a command to perform a thrust that forces a medium towards the relative air opposing aircraft **100**. For example, reverse thrust command may include a thrust of 180 N directed towards the nose of aircraft to at least repel and/or oppose the relative air. Reverse thrust command may alternatively or additionally include any reverse thrust command as described in U.S. Nonprovisional application Ser. No. 17/319,155, filed on May 13, 2021, and entitled "AIRCRAFT HAVING REVERSE THRUST CAPABILITIES," the entirety of which is incorporated herein by reference. In another embodiment, flight controller may be configured to perform a regenerative drag operation. As used in this disclosure a "regenerative drag operation" is an operating condition of an aircraft, wherein the aircraft has a negative thrust and/or is reducing in airspeed velocity. For example, and without limitation, regenerative drag operation may include a positive propeller speed and a negative propeller thrust. Regenerative drag operation may alternatively or additionally include any regenerative drag operation as described in U.S. Nonprovisional application Ser. No. 17/319,155.

[0036] In an embodiment, and still referring to FIG. **1**, flight controller may be configured to perform a corrective action as a function of a failure event. As used in this disclosure a "corrective action" is an action conducted by the plurality of flight components to correct and/or alter a movement of an aircraft. For example, and without limitation, a corrective action may include an action to reduce a yaw torque generated by a failure event. Additionally or alternatively, corrective action may include any corrective action as described in U.S. Nonprovisional application Ser. No. 17/222,539, filed on Apr. 5, 2021, and entitled "AIRCRAFT FOR SELF-NEUTRALIZING FLIGHT," the entirety of which is incorporated herein by reference. As used in this disclosure a "failure event" is a failure of a lift propulsor component of the plurality of lift propulsor components. For example, and without limitation, a failure event may denote a rotation degradation of a rotor, a reduced torque of a rotor, and the like thereof. Additionally or alternatively, failure event may include any failure event as described in U.S. Nonprovisional application Ser. No. 17/113,647, filed on Dec. 7, 2020, and entitled "IN-FLIGHT STABILIZATION OF AN AIRCAFT," the entirety of which is incorporated herein by reference.

[0037] Referring now to FIG. **2**, an exemplary embodiment of an electric aircraft **200** configured to implement a layered data network is illustrated. The electric aircraft **200** includes a first communication component **204**, a second communication component **216** and a third communication component **228**. The first communication component **204** is configured to communicate with a first layer **208** providing radio communication between the electric aircraft **200** and at least a first party **212** at a first bandwidth. The second communication component **216** is configured to communicate with a second layer **220** providing mobile network communication between the electric aircraft **200** and at least a second party **224** at a second bandwidth. The third communication component **228** is configured to communicate with a third layer **232** providing satellite communication between the electric aircraft **200** and at least a third party **236** at a third bandwidth.

[0038] Still referring to FIG. **2**, in an embodiment, aircraft **200** may include a flight controller, an energy source and at least a flight component. These may include any of the flight controllers, energy sources and flight components as described herein.

[0039] With continued reference to FIG. **2**, radio communication between first communication component **204** and first party **212** may be facilitated by one or more radio towers, and the like. Mobile network communication between second communication component **216** and second party may be facilitated by one or more mobile network towers, and the like, among others. Satellite communication

between third communication component **228** and third party **236** may be facilitated by one or more satellites, and the like.

[0040] Still referring to FIG. **2**, the first communication component **204** may include an antenna **240** configured to provide radio communication between the electric aircraft **200** and the at least a first party **212**. For example, and without limitation, the antenna **240** may include a directional antenna configured to provide radio communication between the electric aircraft **200** and the at least a first party **212**. In an embodiment, the first communication component **204** is configured to provide radio communication between the electric aircraft **200** and at least one other aircraft. In another embodiment, the first communication component **204** is configured to provide radio communication between the electric aircraft **200** and at least one recharging station. The first communication component **204** may be configured to provide radio communication in the form of at least one of a voice communication and a video communication. In an embodiment, the at least a first party **212** is different from the at least a second party **224** and the at least a third party **236**. In an embodiment, the first bandwidth is greater than the second bandwidth and the third bandwidth. The second communication component **216** may be configured to provide mobile network communication in the form of at least one of a 4G communication and a 5G communication (and even beyond 5G). In an embodiment, the electric aircraft **200** comprises an electric vertical takeoff and landing (eVTOL) aircraft.

[0041] Still referring to FIG. **2**, radio communication, in accordance with embodiments, may utilize at least a communication band and communication protocols suitable for aircraft radio communication. For example, and without limitation, a very-high-frequency (VHF) airband with frequencies between about 108 MHz and about 137 MHz may be utilized for radio communication. In another example, and without limitation, frequencies in the Gigahertz range may be utilized. Airband or aircraft band is the name for a group of frequencies in the VHF radio spectrum allocated to radio communication in civil aviation, sometimes also referred to as VHF, or phonetically as "Victor". Different sections of the band are used for radio-navigational aids and air traffic control. Radio communication protocols for aircraft are typically governed by the regulations of the Federal Aviation Authority (FAA) in the United States and by other regulatory authorities internationally. Radio communication protocols may employ, for example and without limitation an S band with frequencies in the range from about 2 GHz to about 4 GHz.

[0042] Still referring to FIG. **2**, mobile network communication, in accordance with embodiments, may utilize at least a communication band and communication protocols suitable for aircraft mobile network communication. For example, and without limitation, for 4G mobile network communication frequency bands in the range of about 2 GHz to about 8 GHz may be utilized, and for 5G mobile network communication frequency bands in the ranges of about 450 MHz to about 6 GHz and of about 24 GHz to about 53 GHz may be utilized. Mobile network communication may utilize, for example and without limitation, a mobile network protocol that allows users to move from one network to another with the same IP address.

[0043] Still referring to FIG. **2**, satellite communication, in accordance with embodiments, may utilize at least a communication band and communication protocols suitable for aircraft satellite communication. For example, and without limitation, satellite communication bands may include L-band (1-2 GHz), C-band (4-8 GHz), X-band (8-12 GHz), Ku-band (12-18 GHz), Ku-band (12-18 GHz), and the like, among others. Satellite communication protocols may employ, for example and without limitation, a Secondary Surveillance Radar (SSR) system, automated dependent surveillance-broadcast (ADS-B) system, or the like. In SSR, radar stations may use radar to interrogate transponders attached to or contained in aircraft and receive information in response describing such information as aircraft identity, codes describing flight plans, codes describing destination, and the like SSR may utilize any suitable interrogation mode, including Mode S interrogation for generalized information. ADS-B may implement two communication protocols, ADS-B-Out and ADS-B-In. ADS-B-Out may transmit aircraft position and ADS-B-In may receive aircraft position.

[0044] With continued reference to FIG. **2**, as used in this disclosure a "layered data network" is a data network with a plurality of substantially independent communication layers with each configured to allow for data transfer over predetermined bandwidths and frequencies. As used in this disclosure a "layer" is a distinct and independent functional and procedural tool of transferring data from one location to another. For example, and without limitation, one layer may transmit communication data at a particular frequency range while another layer may transmit communication data at another frequency range such that there is substantially no cross-talk between the two layers which advantageously provides a redundancy and safeguard in the event of a disruption in the operation of one of the layers. The layer may be an abstraction which is not tangible. In an embodiment, the present disclosure provides three substantially independent communication layers which allow for reliable communication between an aircraft and another party.

[0045] Still referring to FIG. **2**, as used in this disclosure a "communication component" is any hardware which facilitates communication between an aircraft and another party. For example, and without limitation, the communication component may include radio communication equipment, mobile or cellular network communication equipment, satellite communication equipment and the like, among others. The radio communication equipment may include any equipment suitable to carry on communication via electromagnetic waves at a particular bandwidth or bandwidth range, for example and without limitation, a receiver, a transmitter, a transceiver, an antenna, an aerial, and the like, among others. The mobile or cellular network communication equipment may include any equipment suitable to carry on communication via electromagnetic waves at a particular bandwidth or bandwidth range, for example and without limitation, a cellular phone, a smart phone, a personal digital assistant (PDA), a tablet, an antenna, an aerial, and the like, among others. The satellite communication equipment may include any equipment suitable to carry on communication via electromagnetic waves at a particular bandwidth or bandwidth range, for example and without limitation, a satellite data unit, an amplifier, an antenna, an aerial, and the like, among others.

[0046] Still referring to FIG. **2**, as used in this disclosure "bandwidth" is measured as the amount of data that can be transferred from one point or location to another in a specific

amount of time. The points or locations may be within a given network. Typically, bandwidth is expressed as a bitrate and measured in bits per second (bps). In some instances, bandwidth may also indicate a range within a band of wavelengths, frequencies, or energies, for example and without limitation, a range of radio frequencies which is utilized for a particular communication.

[0047] Still referring to FIG. **2**, as used in this disclosure "antenna" is a rod, wire, aerial or other device used to transmit or receive signals such as, without limitation, radio signals and the like. A "directional antenna" or beam antenna is an antenna which radiates or receives greater power in specific directions allowing increased performance and reduced interference from unwanted sources. Typical examples of directional antennas include the Yagi antenna, the log-periodic antenna, and the corner reflector antenna. The directional antenna may include a high-gain antenna (HGA) which is a directional antenna with a focused, narrow radio wave beamwidth and a low-gain antenna (LGA) which is an omnidirectional antenna with a broad radio wave beamwidth, as needed or desired.

[0048] Still referring to FIG. **2**, as used in this disclosure "party" is any entity capable of receiving and transmitting data such as from and to an aircraft. The party may be an inanimate object, a human or a combination thereof. For example, the party may be an aircraft, a recharging station, a landing station, an airport, an air traffic control tower, a departure site, a destination site, a radio device, a mobile network device, a satellite device, and the like, among others.

[0049] With continued reference to FIG. **2**, in an embodiment, the first party **212**, the second party **224** and the third party **236** are the same. In another embodiment, each of the first party **212**, the second party **224** and the third party **236** are different. In yet another embodiment, any two of the first party **212**, the second party **224** and the third party **236** are the same while one is different. Thus, in exemplary embodiments, any or all of first, second, and third parties may be the same or different.

[0050] Still referring to FIG. **2**, in an embodiment, the first bandwidth is greater than the second bandwidth, and the second bandwidth is greater than the third bandwidth. In an exemplary embodiment, the first communication component **204** provides S band radio communication. In an exemplary embodiment, the second communication component **216** provides 4G or 5G communication. In an exemplary embodiment, the third communication component **228** provides Satcom communication. Advantageously, the electric aircraft **200**, in accordance with embodiments of the invention, is configured to implement the disclosed layered data network such that a redundant multi-layer data communications system is provided which desirably enhances the reliability and efficacy of communication(s) between the aircraft **200** and one or more other parties, and also provides backup communication mechanism.

[0051] With continued reference to FIG. **2**, in embodiments, electric aircraft **200** is configured to implement a "failover" mechanism whereby the aircraft's communication system is protected from failure and in which standby communication equipment automatically takes over when the main communication system fails. In an embodiment, a flight controller of aircraft **200** may govern and/or manage aircraft communication in the event of a failover. For example, if radio communication is lost, flight controller may be configured with a sensor or the like to detect this and reestablish communication using mobile network communication and/or satellite communication. Flight controller may be equipped to store and/or look up equivalent radio, mobile network and satellite addresses of a party so as to reroute to an alternative communication mode in the event of a failover situation. A database and/or lookup table may be accessible to flight controller for this purpose. Similarly, rerouting between any of the communication modes, that is, radio, mobile network and satellite, may be implemented, as needed or desired. Flight controller may be any of the controllers as disclosed herein and described with reference to at least FIG. **3**.

[0052] Still referring to FIG. **2**, in an embodiment, a lookup table may be used to determine where to send a communication in the event of a failover situation. For example, and without limitation, in the event of a loss of radio communication at a particular frequency or call sign, lookup table can provide an address of and/or information on an alternative channel of communication such as mobile network communication, satellite communication, or both.

[0053] Now referring to FIG. **3**, an exemplary embodiment **300** of a flight controller **304** is illustrated. As used in this disclosure a "flight controller" is a computing device of a plurality of computing devices dedicated to data storage, security, distribution of traffic for load balancing, and flight instruction. Flight controller **304** may include and/or communicate with any computing device as described in this disclosure, including without limitation a microcontroller, microprocessor, digital signal processor (DSP) and/or system on a chip (SoC) as described in this disclosure. Further, flight controller **304** may include a single computing device operating independently, or may include two or more computing device operating in concert, in parallel, sequentially or the like; two or more computing devices may be included together in a single computing device or in two or more computing devices. In embodiments, flight controller **304** may be installed in an aircraft, may control the aircraft remotely, and/or may include an element installed in the aircraft and a remote element in communication therewith.

[0054] In an embodiment, and still referring to FIG. **3**, flight controller **304** may include a signal transformation component **308**. As used in this disclosure a "signal transformation component" is a component that transforms and/or converts a first signal to a second signal, wherein a signal may include one or more digital and/or analog signals. For example, and without limitation, signal transformation component **308** may be configured to perform one or more operations such as preprocessing, lexical analysis, parsing, semantic analysis, and the like thereof. In an embodiment, and without limitation, signal transformation component **308** may include one or more analog-to-digital convertors that transform a first signal of an analog signal to a second signal of a digital signal. For example, and without limitation, an analog-to-digital converter may convert an analog input signal to a 10-bit binary digital representation of that signal. In another embodiment, signal transformation component **308** may include transforming one or more low-level languages such as, but not limited to, machine languages and/or assembly languages. For example, and without limitation, signal transformation component **308** may include transforming a binary language signal to an assembly language signal. In an embodiment, and without limitation, signal transformation component **308** may include trans-

forming one or more high-level languages and/or formal languages such as but not limited to alphabets, strings, and/or languages. For example, and without limitation, high-level languages may include one or more system languages, scripting languages, domain-specific languages, visual languages, esoteric languages, and the like thereof. As a further non-limiting example, high-level languages may include one or more algebraic formula languages, business data languages, string and list languages, object-oriented languages, and the like thereof.

[0055] Still referring to FIG. **3**, signal transformation component **308** may be configured to optimize an intermediate representation **312**. As used in this disclosure an "intermediate representation" is a data structure and/or code that represents the input signal. Signal transformation component **308** may optimize intermediate representation as a function of a data-flow analysis, dependence analysis, alias analysis, pointer analysis, escape analysis, and the like thereof. In an embodiment, and without limitation, signal transformation component **308** may optimize intermediate representation **312** as a function of one or more inline expansions, dead code eliminations, constant propagation, loop transformations, and/or automatic parallelization functions. In another embodiment, signal transformation component **308** may optimize intermediate representation as a function of a machine dependent optimization such as a peephole optimization, wherein a peephole optimization may rewrite short sequences of code into more efficient sequences of code. Signal transformation component **308** may optimize intermediate representation to generate an output language, wherein an "output language," as used herein, is the native machine language of flight controller **304**. For example, and without limitation, native machine language may include one or more binary and/or numerical languages.

[0056] In an embodiment, and without limitation, signal transformation component **308** may include transform one or more inputs and outputs as a function of an error correction code. An error correction code, also known as error correcting code (ECC), is an encoding of a message or lot of data using redundant information, permitting recovery of corrupted data. An ECC may include a block code, in which information is encoded on fixed-size packets and/or blocks of data elements such as symbols of predetermined size, bits, or the like. Reed-Solomon coding, in which message symbols within a symbol set having q symbols are encoded as coefficients of a polynomial of degree less than or equal to a natural number k, over a finite field F with q elements; strings so encoded have a minimum hamming distance of k+1, and permit correction of (q−k−1)/2 erroneous symbols. Block code may alternatively or additionally be implemented using Golay coding, also known as binary Golay coding, Bose-Chaudhuri, Hocquenghuem (BCH) coding, multidimensional parity-check coding, and/or Hamming codes. An ECC may alternatively or additionally be based on a convolutional code.

[0057] In an embodiment, and still referring to FIG. **3**, flight controller **304** may include a reconfigurable hardware platform **316**. A "reconfigurable hardware platform," as used herein, is a component and/or unit of hardware that may be reprogrammed, such that, for instance, a data path between elements such as logic gates or other digital circuit elements may be modified to change an algorithm, state, logical sequence, or the like of the component and/or unit. This may be accomplished with such flexible high-speed computing fabrics as field-programmable gate arrays (FPGAs), which may include a grid of interconnected logic gates, connections between which may be severed and/or restored to program in modified logic. Reconfigurable hardware platform **316** may be reconfigured to enact any algorithm and/or algorithm selection process received from another computing device and/or created using machine-learning processes.

[0058] Still referring to FIG. **3**, reconfigurable hardware platform **316** may include a logic component **320**. As used in this disclosure a "logic component" is a component that executes instructions on output language. For example, and without limitation, logic component may perform basic arithmetic, logic, controlling, input/output operations, and the like thereof. Logic component **320** may include any suitable processor, such as without limitation a component incorporating logical circuitry for performing arithmetic and logical operations, such as an arithmetic and logic unit (ALU), which may be regulated with a state machine and directed by operational inputs from memory and/or sensors; logic component **320** may be organized according to Von Neumann and/or Harvard architecture as a non-limiting example. Logic component **320** may include, incorporate, and/or be incorporated in, without limitation, a microcontroller, microprocessor, digital signal processor (DSP), Field Programmable Gate Array (FPGA), Complex Programmable Logic Device (CPLD), Graphical Processing Unit (GPU), general purpose GPU, Tensor Processing Unit (TPU), analog or mixed signal processor, Trusted Platform Module (TPM), a floating point unit (FPU), and/or system on a chip (SoC). In an embodiment, logic component **320** may include one or more integrated circuit microprocessors, which may contain one or more central processing units, central processors, and/or main processors, on a single metal-oxide-semiconductor chip. Logic component **320** may be configured to execute a sequence of stored instructions to be performed on the output language and/or intermediate representation **312**. Logic component **320** may be configured to fetch and/or retrieve the instruction from a memory cache, wherein a "memory cache," as used in this disclosure, is a stored instruction set on flight controller **304**. Logic component **320** may be configured to decode the instruction retrieved from the memory cache to opcodes and/or operands. Logic component **320** may be configured to execute the instruction on intermediate representation **312** and/or output language. For example, and without limitation, logic component **320** may be configured to execute an addition operation on intermediate representation **312** and/or output language.

[0059] In an embodiment, and without limitation, logic component **320** may be configured to calculate a flight element **324**. As used in this disclosure a "flight element" is an element of datum denoting a relative status of aircraft. For example, and without limitation, flight element **324** may denote one or more torques, thrusts, airspeed velocities, forces, altitudes, groundspeed velocities, directions during flight, directions facing, forces, orientations, and the like thereof. For example, and without limitation, flight element **324** may denote that aircraft is cruising at an altitude and/or with a sufficient magnitude of forward thrust. As a further non-limiting example, flight status may denote that is building thrust and/or groundspeed velocity in preparation for a

takeoff. As a further non-limiting example, flight element **324** may denote that aircraft is following a flight path accurately and/or sufficiently.

[0060] Still referring to FIG. **3**, flight controller **304** may include a chipset component **328**. As used in this disclosure a "chipset component" is a component that manages data flow. In an embodiment, and without limitation, chipset component **328** may include a northbridge data flow path, wherein the northbridge dataflow path may manage data flow from logic component **320** to a high-speed device and/or component, such as a RAM, graphics controller, and the like thereof. In another embodiment, and without limitation, chipset component **328** may include a southbridge data flow path, wherein the southbridge dataflow path may manage data flow from logic component **320** to lower-speed peripheral buses, such as a peripheral component interconnect (PCI), industry standard architecture (ICA), and the like thereof. In an embodiment, and without limitation, southbridge data flow path may include managing data flow between peripheral connections such as ethernet, USB, audio devices, and the like thereof. Additionally or alternatively, chipset component **328** may manage data flow between logic component **320**, memory cache, and a flight component **108**. As used in this disclosure a "flight component" is a portion of an aircraft that can be moved or adjusted to affect one or more flight elements. For example, flight component **108** may include a component used to affect the aircrafts' roll and pitch which may comprise one or more ailerons. As a further example, flight component **108** may include a rudder to control yaw of an aircraft. In an embodiment, chipset component **328** may be configured to communicate with a plurality of flight components as a function of flight element **324**. For example, and without limitation, chipset component **328** may transmit to an aircraft rotor to reduce torque of a first lift propulsor and increase the forward thrust produced by a pusher component to perform a flight maneuver.

[0061] In an embodiment, and still referring to FIG. **3**, flight controller **304** may be configured generate an autonomous function. As used in this disclosure an "autonomous function" is a mode and/or function of flight controller **304** that controls aircraft automatically. For example, and without limitation, autonomous function may perform one or more aircraft maneuvers, take offs, landings, altitude adjustments, flight leveling adjustments, turns, climbs, and/or descents. As a further non-limiting example, autonomous function may adjust one or more airspeed velocities, thrusts, torques, and/or groundspeed velocities. As a further non-limiting example, autonomous function may perform one or more flight path corrections and/or flight path modifications as a function of flight element **324**. In an embodiment, autonomous function may include one or more modes of autonomy such as, but not limited to, autonomous mode, semi-autonomous mode, and/or non-autonomous mode. As used in this disclosure "autonomous mode" is a mode that automatically adjusts and/or controls aircraft and/or the maneuvers of aircraft in its entirety. For example, autonomous mode may denote that flight controller **304** will adjust the aircraft. As used in this disclosure a "semi-autonomous mode" is a mode that automatically adjusts and/or controls a portion and/or section of aircraft. For example, and without limitation, semi-autonomous mode may denote that a pilot will control the propulsors, wherein flight controller **304** will control the ailerons and/or rudders. As used in this disclosure "non-autonomous mode" is a mode that denotes a pilot will control aircraft and/or maneuvers of aircraft in its entirety.

[0062] In an embodiment, and still referring to FIG. **3**, flight controller **304** may generate autonomous function as a function of an autonomous machine-learning model. As used in this disclosure an "autonomous machine-learning model" is a machine-learning model to produce an autonomous function output given flight element **324** and a pilot signal **336** as inputs; this is in contrast to a non-machine learning software program where the commands to be executed are determined in advance by a user and written in a programming language. As used in this disclosure a "pilot signal" is an element of datum representing one or more functions a pilot is controlling and/or adjusting. For example, pilot signal **336** may denote that a pilot is controlling and/or maneuvering ailerons, wherein the pilot is not in control of the rudders and/or propulsors. In an embodiment, pilot signal **336** may include an implicit signal and/or an explicit signal. For example, and without limitation, pilot signal **336** may include an explicit signal, wherein the pilot explicitly states there is a lack of control and/or desire for autonomous function. As a further non-limiting example, pilot signal **336** may include an explicit signal directing flight controller **304** to control and/or maintain a portion of aircraft, a portion of the flight plan, the entire aircraft, and/or the entire flight plan. As a further non-limiting example, pilot signal **336** may include an implicit signal, wherein flight controller **304** detects a lack of control such as by a malfunction, torque alteration, flight path deviation, and the like thereof. In an embodiment, and without limitation, pilot signal **336** may include one or more explicit signals to reduce torque, and/or one or more implicit signals that torque may be reduced due to reduction of airspeed velocity. In an embodiment, and without limitation, pilot signal **336** may include one or more local and/or global signals. For example, and without limitation, pilot signal **336** may include a local signal that is transmitted by a pilot and/or crew member. As a further non-limiting example, pilot signal **336** may include a global signal that is transmitted by air traffic control and/or one or more remote users that are in communication with the pilot of aircraft. In an embodiment, pilot signal **336** may be received as a function of a tri-state bus and/or multiplexor that denotes an explicit pilot signal should be transmitted prior to any implicit or global pilot signal.

[0063] Still referring to FIG. **3**, autonomous machine-learning model may include one or more autonomous machine-learning processes such as supervised, unsupervised, or reinforcement machine-learning processes that flight controller **304** and/or a remote device may or may not use in the generation of autonomous function. As used in this disclosure "remote device" is an external device to flight controller **304**. Additionally or alternatively, autonomous machine-learning model may include one or more autonomous machine-learning processes that a field-programmable gate array (FPGA) may or may not use in the generation of autonomous function. Autonomous machine-learning process may include, without limitation machine learning processes such as simple linear regression, multiple linear regression, polynomial regression, support vector regression, ridge regression, lasso regression, elasticnet regression, decision tree regression, random forest regression, logistic regression, logistic classification, K-nearest neigh-

bors, support vector machines, kernel support vector machines, naïve bayes, decision tree classification, random forest classification, K-means clustering, hierarchical clustering, dimensionality reduction, principal component analysis, linear discriminant analysis, kernel principal component analysis, Q-learning, State Action Reward State Action (SARSA), Deep-Q network, Markov decision processes, Deep Deterministic Policy Gradient (DDPG), or the like thereof.

[0064] In an embodiment, and still referring to FIG. **3**, autonomous machine learning model may be trained as a function of autonomous training data, wherein autonomous training data may correlate a flight element, pilot signal, and/or simulation data to an autonomous function. For example, and without limitation, a flight element of an airspeed velocity, a pilot signal of limited and/or no control of propulsors, and a simulation data of required airspeed velocity to reach the destination may result in an autonomous function that includes a semi-autonomous mode to increase thrust of the propulsors. Autonomous training data may be received as a function of user-entered valuations of flight elements, pilot signals, simulation data, and/or autonomous functions. Flight controller **304** may receive autonomous training data by receiving correlations of flight element, pilot signal, and/or simulation data to an autonomous function that were previously received and/or determined during a previous iteration of generation of autonomous function. Autonomous training data may be received by one or more remote devices and/or FPGAs that at least correlate a flight element, pilot signal, and/or simulation data to an autonomous function. Autonomous training data may be received in the form of one or more user-entered correlations of a flight element, pilot signal, and/or simulation data to an autonomous function.

[0065] Still referring to FIG. **3**, flight controller **304** may receive autonomous machine-learning model from a remote device and/or FPGA that utilizes one or more autonomous machine learning processes, wherein a remote device and an FPGA is described above in detail. For example, and without limitation, a remote device may include a computing device, external device, processor, FPGA, microprocessor and the like thereof. Remote device and/or FPGA may perform the autonomous machine-learning process using autonomous training data to generate autonomous function and transmit the output to flight controller **304**. Remote device and/or FPGA may transmit a signal, bit, datum, or parameter to flight controller **304** that at least relates to autonomous function. Additionally or alternatively, the remote device and/or FPGA may provide an updated machine-learning model. For example, and without limitation, an updated machine-learning model may be comprised of a firmware update, a software update, an autonomous machine-learning process correction, and the like thereof. As a non-limiting example a software update may incorporate a new simulation data that relates to a modified flight element. Additionally or alternatively, the updated machine learning model may be transmitted to the remote device and/or FPGA, wherein the remote device and/or FPGA may replace the autonomous machine-learning model with the updated machine-learning model and generate the autonomous function as a function of the flight element, pilot signal, and/or simulation data using the updated machine-learning model. The updated machine-learning model may be transmitted by the remote device and/or FPGA and received by flight controller **304** as a software update, firmware update, or corrected autonomous machine-learning model. For example, and without limitation autonomous machine learning model may utilize a neural net machine-learning process, wherein the updated machine-learning model may incorporate a gradient boosting machine-learning process.

[0066] Still referring to FIG. **3**, flight controller **304** may include, be included in, and/or communicate with a mobile device such as a mobile telephone or smartphone. Further, flight controller may communicate with one or more additional devices as described below in further detail via a network interface device. The network interface device may be utilized for commutatively connecting a flight controller to one or more of a variety of networks, and one or more devices. Examples of a network interface device include, but are not limited to, a network interface card (e.g., a mobile network interface card, a LAN card), a modem, and any combination thereof. Examples of a network include, but are not limited to, a wide area network (e.g., the Internet, an enterprise network), a local area network (e.g., a network associated with an office, a building, a campus or other relatively small geographic space), a telephone network, a data network associated with a telephone/voice provider (e.g., a mobile communications provider data and/or voice network), a direct connection between two computing devices, and any combinations thereof. The network may include any network topology and can may employ a wired and/or a wireless mode of communication.

[0067] In an embodiment, and still referring to FIG. **3**, flight controller **304** may include, but is not limited to, for example, a cluster of flight controllers in a first location and a second flight controller or cluster of flight controllers in a second location. Flight controller **304** may include one or more flight controllers dedicated to data storage, security, distribution of traffic for load balancing, and the like. Flight controller **304** may be configured to distribute one or more computing tasks as described below across a plurality of flight controllers, which may operate in parallel, in series, redundantly, or in any other manner used for distribution of tasks or memory between computing devices. For example, and without limitation, flight controller **304** may implement a control algorithm to distribute and/or command the plurality of flight controllers. As used in this disclosure a "control algorithm" is a finite sequence of well-defined computer implementable instructions that may determine the flight component of the plurality of flight components to be adjusted. For example, and without limitation, control algorithm may include one or more algorithms that reduce and/or prevent aviation asymmetry. As a further non-limiting example, control algorithms may include one or more models generated as a function of a software including, but not limited to Simulink by MathWorks, Natick, Mass., USA. In an embodiment, and without limitation, control algorithm may be configured to generate an auto-code, wherein an "auto-code," is used herein, is a code and/or algorithm that is generated as a function of the one or more models and/or software's. In another embodiment, control algorithm may be configured to produce a segmented control algorithm. As used in this disclosure a "segmented control algorithm" is control algorithm that has been separated and/or parsed into discrete sections. For example, and without limitation, segmented control algorithm may parse control algorithm into two or more segments, wherein each segment of control

algorithm may be performed by one or more flight controllers operating on distinct flight components.

[0068] In an embodiment, and still referring to FIG. **3**, control algorithm may be configured to determine a segmentation boundary as a function of segmented control algorithm. As used in this disclosure a "segmentation boundary" is a limit and/or delineation associated with the segments of the segmented control algorithm. For example, and without limitation, segmentation boundary may denote that a segment in the control algorithm has a first starting section and/or a first ending section. As a further non-limiting example, segmentation boundary may include one or more boundaries associated with an ability of flight component **108**. In an embodiment, control algorithm may be configured to create an optimized signal communication as a function of segmentation boundary. For example, and without limitation, optimized signal communication may include identifying the discrete timing required to transmit and/or receive the one or more segmentation boundaries. In an embodiment, and without limitation, creating optimized signal communication further comprises separating a plurality of signal codes across the plurality of flight controllers. For example, and without limitation the plurality of flight controllers may include one or more formal networks, wherein formal networks transmit data along an authority chain and/or are limited to task-related communications. As a further non-limiting example, communication network may include informal networks, wherein informal networks transmit data in any direction. In an embodiment, and without limitation, the plurality of flight controllers may include a chain path, wherein a "chain path," as used herein, is a linear communication path comprising a hierarchy that data may flow through. In an embodiment, and without limitation, the plurality of flight controllers may include an all-channel path, wherein an "all-channel path," as used herein, is a communication path that is not restricted to a particular direction. For example, and without limitation, data may be transmitted upward, downward, laterally, and the like thereof. In an embodiment, and without limitation, the plurality of flight controllers may include one or more neural networks that assign a weighted value to a transmitted datum. For example, and without limitation, a weighted value may be assigned as a function of one or more signals denoting that a flight component is malfunctioning and/or in a failure state.

[0069] Still referring to FIG. **3**, the plurality of flight controllers may include a master bus controller. As used in this disclosure a "master bus controller" is one or more devices and/or components that are connected to a bus to initiate a direct memory access transaction, wherein a bus is one or more terminals in a bus architecture. Master bus controller may communicate using synchronous and/or asynchronous bus control protocols. In an embodiment, master bus controller may include flight controller **304**. In another embodiment, master bus controller may include one or more universal asynchronous receiver-transmitters (UART). For example, and without limitation, master bus controller may include one or more bus architectures that allow a bus to initiate a direct memory access transaction from one or more buses in the bus architectures. As a further non-limiting example, master bus controller may include one or more peripheral devices and/or components to communicate with another peripheral device and/or component and/or the master bus controller. In an embodiment, master bus controller may be configured to perform bus arbitration. As used in this disclosure "bus arbitration" is method and/or scheme to prevent multiple buses from attempting to communicate with and/or connect to master bus controller. For example and without limitation, bus arbitration may include one or more schemes such as a small computer interface system, wherein a small computer interface system is a set of standards for physical connecting and transferring data between peripheral devices and master bus controller by defining commands, protocols, electrical, optical, and/or logical interfaces. In an embodiment, master bus controller may receive intermediate representation **312** and/or output language from logic component **320**, wherein output language may include one or more analog-to-digital conversions, low bit rate transmissions, message encryptions, digital signals, binary signals, logic signals, analog signals, and the like thereof described above in detail.

[0070] Still referring to FIG. **3**, master bus controller may communicate with a slave bus. As used in this disclosure a "slave bus" is one or more peripheral devices and/or components that initiate a bus transfer. For example, and without limitation, slave bus may receive one or more controls and/or asymmetric communications from master bus controller, wherein slave bus transfers data stored to master bus controller. In an embodiment, and without limitation, slave bus may include one or more internal buses, such as but not limited to a/an internal data bus, memory bus, system bus, front-side bus, and the like thereof. In another embodiment, and without limitation, slave bus may include one or more external buses such as external flight controllers, external computers, remote devices, printers, aircraft computer systems, flight control systems, and the like thereof.

[0071] In an embodiment, and still referring to FIG. **3**, control algorithm may optimize signal communication as a function of determining one or more discrete timings. For example, and without limitation master bus controller may synchronize timing of the segmented control algorithm by injecting high priority timing signals on a bus of the master bus control. As used in this disclosure a "high priority timing signal" is information denoting that the information is important. For example, and without limitation, high priority timing signal may denote that a section of control algorithm is of high priority and should be analyzed and/or transmitted prior to any other sections being analyzed and/or transmitted. In an embodiment, high priority timing signal may include one or more priority packets. As used in this disclosure a "priority packet" is a formatted unit of data that is communicated between the plurality of flight controllers. For example, and without limitation, priority packet may denote that a section of control algorithm should be used and/or is of greater priority than other sections.

[0072] Still referring to FIG. **3**, flight controller **304** may also be implemented using a "shared nothing" architecture in which data is cached at the worker, in an embodiment, this may enable scalability of aircraft and/or computing device. Flight controller **304** may include a distributer flight controller. As used in this disclosure a "distributer flight controller" is a component that adjusts and/or controls a plurality of flight components as a function of a plurality of flight controllers. For example, distributer flight controller may include a flight controller that communicates with a plurality of additional flight controllers and/or clusters of flight controllers. In an embodiment, distributed flight control may include one or more neural networks. For example,

neural network also known as an artificial neural network, is a network of "nodes," or data structures having one or more inputs, one or more outputs, and a function determining outputs based on inputs. Such nodes may be organized in a network, such as without limitation a convolutional neural network, including an input layer of nodes, one or more intermediate layers, and an output layer of nodes. Connections between nodes may be created via the process of "training" the network, in which elements from a training dataset are applied to the input nodes, a suitable training algorithm (such as Levenberg-Marquardt, conjugate gradient, simulated annealing, or other algorithms) is then used to adjust the connections and weights between nodes in adjacent layers of the neural network to produce the desired values at the output nodes. This process is sometimes referred to as deep learning.

[0073] Still referring to FIG. **3**, a node may include, without limitation a plurality of inputs x_i that may receive numerical values from inputs to a neural network containing the node and/or from other nodes. Node may perform a weighted sum of inputs using weights w_i that are multiplied by respective inputs x_i. Additionally or alternatively, a bias b may be added to the weighted sum of the inputs such that an offset is added to each unit in the neural network layer that is independent of the input to the layer. The weighted sum may then be input into a function φ, which may generate one or more outputs y. Weight w_i applied to an input x_i may indicate whether the input is "excitatory," indicating that it has strong influence on the one or more outputs y, for instance by the corresponding weight having a large numerical value, and/or a "inhibitory," indicating it has a weak effect influence on the one more inputs y, for instance by the corresponding weight having a small numerical value. The values of weights w_i may be determined by training a neural network using training data, which may be performed using any suitable process as described above. In an embodiment, and without limitation, a neural network may receive semantic units as inputs and output vectors representing such semantic units according to weights w_i that are derived using machine-learning processes as described in this disclosure.

[0074] Still referring to FIG. **3**, flight controller may include a sub-controller **340**. As used in this disclosure a "sub-controller" is a controller and/or component that is part of a distributed controller as described above; for instance, flight controller **304** may be and/or include a distributed flight controller made up of one or more sub-controllers. For example, and without limitation, sub-controller **340** may include any controllers and/or components thereof that are similar to distributed flight controller and/or flight controller as described above. Sub-controller **340** may include any component of any flight controller as described above. Sub-controller **340** may be implemented in any manner suitable for implementation of a flight controller as described above. As a further non-limiting example, sub-controller **340** may include one or more processors, logic components and/or computing devices capable of receiving, processing, and/or transmitting data across the distributed flight controller as described above. As a further non-limiting example, sub-controller **340** may include a controller that receives a signal from a first flight controller and/or first distributed flight controller component and transmits the signal to a plurality of additional sub-controllers and/or flight components.

[0075] Still referring to FIG. **3**, flight controller may include a co-controller **344**. As used in this disclosure a "co-controller" is a controller and/or component that joins flight controller **304** as components and/or nodes of a distributer flight controller as described above. For example, and without limitation, co-controller **344** may include one or more controllers and/or components that are similar to flight controller **304**. As a further non-limiting example, co-controller **344** may include any controller and/or component that joins flight controller **304** to distributer flight controller. As a further non-limiting example, co-controller **344** may include one or more processors, logic components and/or computing devices capable of receiving, processing, and/or transmitting data to and/or from flight controller **304** to distributed flight control system. Co-controller **344** may include any component of any flight controller as described above. Co-controller **344** may be implemented in any manner suitable for implementation of a flight controller as described above.

[0076] In an embodiment, and with continued reference to FIG. **3**, flight controller **304** may be designed and/or configured to perform any method, method step, or sequence of method steps in any embodiment described in this disclosure, in any order and with any degree of repetition. For instance, flight controller **304** may be configured to perform a single step or sequence repeatedly until a desired or commanded outcome is achieved; repetition of a step or a sequence of steps may be performed iteratively and/or recursively using outputs of previous repetitions as inputs to subsequent repetitions, aggregating inputs and/or outputs of repetitions to produce an aggregate result, reduction or decrement of one or more variables such as global variables, and/or division of a larger processing task into a set of iteratively addressed smaller processing tasks. Flight controller may perform any step or sequence of steps as described in this disclosure in parallel, such as simultaneously and/or substantially simultaneously performing a step two or more times using two or more parallel threads, processor cores, or the like; division of tasks between parallel threads and/or processes may be performed according to any protocol suitable for division of tasks between iterations. Persons skilled in the art, upon reviewing the entirety of this disclosure, will be aware of various ways in which steps, sequences of steps, processing tasks, and/or data may be subdivided, shared, or otherwise dealt with using iteration, recursion, and/or parallel processing.

[0077] Referring now to FIG. **4**, an exemplary embodiment of a machine-learning module **400** that may perform one or more machine-learning processes as described in this disclosure is illustrated. Machine-learning module may perform determinations, classification, and/or analysis steps, methods, processes, or the like as described in this disclosure using machine learning processes. A "machine learning process," as used in this disclosure, is a process that automatedly uses training data **404** to generate an algorithm that will be performed by a computing device/module to produce outputs **408** given data provided as inputs **412**; this is in contrast to a non-machine learning software program where the commands to be executed are determined in advance by a user and written in a programming language.

[0078] Still referring to FIG. **4**, "training data," as used herein, is data containing correlations that a machine-learning process may use to model relationships between two or more categories of data elements. For instance, and without

limitation, training data **404** may include a plurality of data entries, each entry representing a set of data elements that were recorded, received, and/or generated together; data elements may be correlated by shared existence in a given data entry, by proximity in a given data entry, or the like. Multiple data entries in training data **404** may evince one or more trends in correlations between categories of data elements; for instance, and without limitation, a higher value of a first data element belonging to a first category of data element may tend to correlate to a higher value of a second data element belonging to a second category of data element, indicating a possible proportional or other mathematical relationship linking values belonging to the two categories. Multiple categories of data elements may be related in training data **404** according to various correlations; correlations may indicate causative and/or predictive links between categories of data elements, which may be modeled as relationships such as mathematical relationships by machine-learning processes as described in further detail below. Training data **404** may be formatted and/or organized by categories of data elements, for instance by associating data elements with one or more descriptors corresponding to categories of data elements. As a non-limiting example, training data **404** may include data entered in standardized forms by persons or processes, such that entry of a given data element in a given field in a form may be mapped to one or more descriptors of categories. Elements in training data **404** may be linked to descriptors of categories by tags, tokens, or other data elements; for instance, and without limitation, training data **404** may be provided in fixed-length formats, formats linking positions of data to categories such as comma-separated value (CSV) formats and/or self-describing formats such as extensible markup language (XML), JavaScript Object Notation (JSON), or the like, enabling processes or devices to detect categories of data.

[0079] Alternatively or additionally, and continuing to refer to FIG. **4**, training data **404** may include one or more elements that are not categorized; that is, training data **404** may not be formatted or contain descriptors for some elements of data. Machine-learning algorithms and/or other processes may sort training data **404** according to one or more categorizations using, for instance, natural language processing algorithms, tokenization, detection of correlated values in raw data and the like; categories may be generated using correlation and/or other processing algorithms. As a non-limiting example, in a corpus of text, phrases making up a number "n" of compound words, such as nouns modified by other nouns, may be identified according to a statistically significant prevalence of n-grams containing such words in a particular order; such an n-gram may be categorized as an element of language such as a "word" to be tracked similarly to single words, generating a new category as a result of statistical analysis. Similarly, in a data entry including some textual data, a person's name may be identified by reference to a list, dictionary, or other compendium of terms, permitting ad-hoc categorization by machine-learning algorithms, and/or automated association of data in the data entry with descriptors or into a given format. The ability to categorize data entries automatedly may enable the same training data **404** to be made applicable for two or more distinct machine-learning algorithms as described in further detail below. Training data **404** used by machine-learning module **400** may correlate any input data as described in this disclosure to any output data as described in this disclosure. As a non-limiting illustrative example flight elements and/or pilot signals may be inputs, wherein an output may be an autonomous function.

[0080] Further referring to FIG. **4**, training data may be filtered, sorted, and/or selected using one or more supervised and/or unsupervised machine-learning processes and/or models as described in further detail below; such models may include without limitation a training data classifier **416**. Training data classifier **416** may include a "classifier," which as used in this disclosure is a machine-learning model as defined below, such as a mathematical model, neural net, or program generated by a machine learning algorithm known as a "classification algorithm," as described in further detail below, that sorts inputs into categories or bins of data, outputting the categories or bins of data and/or labels associated therewith. A classifier may be configured to output at least a datum that labels or otherwise identifies a set of data that are clustered together, found to be close under a distance metric as described below, or the like. Machine-learning module **400** may generate a classifier using a classification algorithm, defined as a processes whereby a computing device and/or any module and/or component operating thereon derives a classifier from training data **404**. Classification may be performed using, without limitation, linear classifiers such as without limitation logistic regression and/or naive Bayes classifiers, nearest neighbor classifiers such as k-nearest neighbors classifiers, support vector machines, least squares support vector machines, fisher's linear discriminant, quadratic classifiers, decision trees, boosted trees, random forest classifiers, learning vector quantization, and/or neural network-based classifiers. As a non-limiting example, training data classifier **416** may classify elements of training data to sub-categories of flight elements such as torques, forces, thrusts, directions, and the like thereof.

[0081] Still referring to FIG. **4**, machine-learning module **400** may be configured to perform a lazy-learning process **420** and/or protocol, which may alternatively be referred to as a "lazy loading" or "call-when-needed" process and/or protocol, may be a process whereby machine learning is conducted upon receipt of an input to be converted to an output, by combining the input and training set to derive the algorithm to be used to produce the output on demand. For instance, an initial set of simulations may be performed to cover an initial heuristic and/or "first guess" at an output and/or relationship. As a non-limiting example, an initial heuristic may include a ranking of associations between inputs and elements of training data **404**. Heuristic may include selecting some number of highest-ranking associations and/or training data **404** elements. Lazy learning may implement any suitable lazy learning algorithm, including without limitation a K-nearest neighbors algorithm, a lazy naïve Bayes algorithm, or the like; persons skilled in the art, upon reviewing the entirety of this disclosure, will be aware of various lazy-learning algorithms that may be applied to generate outputs as described in this disclosure, including without limitation lazy learning applications of machine-learning algorithms as described in further detail below.

[0082] Alternatively or additionally, and with continued reference to FIG. **4**, machine-learning processes as described in this disclosure may be used to generate machine-learning models **424**. A "machine-learning model," as used in this disclosure, is a mathematical and/or algorithmic representation of a relationship between inputs and outputs, as

generated using any machine-learning process including without limitation any process as described above, and stored in memory; an input is submitted to a machine-learning model **424** once created, which generates an output based on the relationship that was derived. For instance, and without limitation, a linear regression model, generated using a linear regression algorithm, may compute a linear combination of input data using coefficients derived during machine-learning processes to calculate an output datum. As a further non-limiting example, a machine-learning model **424** may be generated by creating an artificial neural network, such as a convolutional neural network comprising an input layer of nodes, one or more intermediate layers, and an output layer of nodes. Connections between nodes may be created via the process of "training" the network, in which elements from a training data **404** set are applied to the input nodes, a suitable training algorithm (such as Levenberg-Marquardt, conjugate gradient, simulated annealing, or other algorithms) is then used to adjust the connections and weights between nodes in adjacent layers of the neural network to produce the desired values at the output nodes. This process is sometimes referred to as deep learning.

[0083] Still referring to FIG. **4**, machine-learning algorithms may include at least a supervised machine-learning process **428**. At least a supervised machine-learning process **428**, as defined herein, include algorithms that receive a training set relating a number of inputs to a number of outputs, and seek to find one or more mathematical relations relating inputs to outputs, where each of the one or more mathematical relations is optimal according to some criterion specified to the algorithm using some scoring function. For instance, a supervised learning algorithm may include flight elements and/or pilot signals as described above as inputs, autonomous functions as outputs, and a scoring function representing a desired form of relationship to be detected between inputs and outputs; scoring function may, for instance, seek to maximize the probability that a given input and/or combination of elements inputs is associated with a given output to minimize the probability that a given input is not associated with a given output. Scoring function may be expressed as a risk function representing an "expected loss" of an algorithm relating inputs to outputs, where loss is computed as an error function representing a degree to which a prediction generated by the relation is incorrect when compared to a given input-output pair provided in training data **404**. Persons skilled in the art, upon reviewing the entirety of this disclosure, will be aware of various possible variations of at least a supervised machine-learning process **428** that may be used to determine relation between inputs and outputs. Supervised machine-learning processes may include classification algorithms as defined above.

[0084] Further referring to FIG. **4**, machine learning processes may include at least an unsupervised machine-learning processes **432**. An unsupervised machine-learning process, as used herein, is a process that derives inferences in datasets without regard to labels; as a result, an unsupervised machine-learning process may be free to discover any structure, relationship, and/or correlation provided in the data. Unsupervised processes may not require a response variable; unsupervised processes may be used to find interesting patterns and/or inferences between variables, to determine a degree of correlation between two or more variables, or the like.

[0085] Still referring to FIG. **4**, machine-learning module **400** may be designed and configured to create a machine-learning model **424** using techniques for development of linear regression models. Linear regression models may include ordinary least squares regression, which aims to minimize the square of the difference between predicted outcomes and actual outcomes according to an appropriate norm for measuring such a difference (e.g. a vector-space distance norm); coefficients of the resulting linear equation may be modified to improve minimization. Linear regression models may include ridge regression methods, where the function to be minimized includes the least-squares function plus term multiplying the square of each coefficient by a scalar amount to penalize large coefficients. Linear regression models may include least absolute shrinkage and selection operator (LASSO) models, in which ridge regression is combined with multiplying the least-squares term by a factor of 1 divided by double the number of samples. Linear regression models may include a multi-task lasso model wherein the norm applied in the least-squares term of the lasso model is the Frobenius norm amounting to the square root of the sum of squares of all terms. Linear regression models may include the elastic net model, a multi-task elastic net model, a least angle regression model, a LARS lasso model, an orthogonal matching pursuit model, a Bayesian regression model, a logistic regression model, a stochastic gradient descent model, a perceptron model, a passive aggressive algorithm, a robustness regression model, a Huber regression model, or any other suitable model that may occur to persons skilled in the art upon reviewing the entirety of this disclosure. Linear regression models may be generalized in an embodiment to polynomial regression models, whereby a polynomial equation (e.g. a quadratic, cubic or higher-order equation) providing a best predicted output/actual output fit is sought; similar methods to those described above may be applied to minimize error functions, as will be apparent to persons skilled in the art upon reviewing the entirety of this disclosure.

[0086] Continuing to refer to FIG. **4**, machine-learning algorithms may include, without limitation, linear discriminant analysis. Machine-learning algorithm may include quadratic discriminate analysis. Machine-learning algorithms may include kernel ridge regression. Machine-learning algorithms may include support vector machines, including without limitation support vector classification-based regression processes. Machine-learning algorithms may include stochastic gradient descent algorithms, including classification and regression algorithms based on stochastic gradient descent. Machine-learning algorithms may include nearest neighbors algorithms. Machine-learning algorithms may include Gaussian processes such as Gaussian Process Regression. Machine-learning algorithms may include cross-decomposition algorithms, including partial least squares and/or canonical correlation analysis. Machine-learning algorithms may include naïve Bayes methods. Machine-learning algorithms may include algorithms based on decision trees, such as decision tree classification or regression algorithms. Machine-learning algorithms may include ensemble methods such as bagging meta-estimator, forest of randomized tress, AdaBoost, gradient tree boosting, and/or voting classifier methods. Machine-learning algorithms may include neural net algorithms, including convolutional neural net processes.

[0087] Now referring to FIG. **5**, an exemplary embodiment of a method **500** to implement a layered data network in electric aircraft is illustrated. In an embodiment, and without limitation, the aircraft may be an electric vertical takeoff and landing (eVTOL) aircraft. The steps of method **500** may be performed in series, in parallel, in a combination thereof, and in any other sequence of steps as disclosed herein.

[0088] Still referring to FIG. **5**, at step **504** communication is provided with a first layer which provides radio communication between the electric aircraft and at least a first party at a first bandwidth. In an embodiment, this communication is by a first communication component of the electric aircraft. The first layer, the first bandwidth, the first party and the first communication component may include any one of those as disclosed herein and described above with reference to at least FIG. **2**.

[0089] Still referring to FIG. **5**, at step **508** communication is provided with a second layer which provides mobile network communication between the electric aircraft and at least a second party at a second bandwidth. In an embodiment, this communication is by a second communication component of the electric aircraft. The second layer, the second bandwidth, the second party and the second communication component may include any one of those as disclosed herein and described above with reference to at least FIG. **2**.

[0090] Still referring to FIG. **5**, at step **512** communication is provided with a third layer which provides satellite communication between the electric aircraft and at least a third party at a second bandwidth. In an embodiment, this communication is by a third communication component of the electric aircraft. The third layer, the third bandwidth, the third party and the third communication component may include any one of those as disclosed herein and described above with reference to at least FIG. **2**.

[0091] It is to be noted that any one or more of the aspects and embodiments described herein may be conveniently implemented using one or more machines (e.g., one or more computing devices that are utilized as a user computing device for an electronic document, one or more server devices, such as a document server, etc.) programmed according to the teachings of the present specification, as will be apparent to those of ordinary skill in the computer art. Appropriate software coding can readily be prepared by skilled programmers based on the teachings of the present disclosure, as will be apparent to those of ordinary skill in the software art. Aspects and implementations discussed above employing software and/or software modules may also include appropriate hardware for assisting in the implementation of the machine executable instructions of the software and/or software module.

[0092] Such software may be a computer program product that employs a machine-readable storage medium. A machine-readable storage medium may be any medium that is capable of storing and/or encoding a sequence of instructions for execution by a machine (e.g., a computing device) and that causes the machine to perform any one of the methodologies and/or embodiments described herein. Examples of a machine-readable storage medium include, but are not limited to, a magnetic disk, an optical disc (e.g., CD, CD-R, DVD, DVD-R, etc.), a magneto-optical disk, a read-only memory "ROM" device, a random access memory "RAM" device, a magnetic card, an optical card, a solid-state memory device, an EPROM, an EEPROM, and any combinations thereof. A machine-readable medium, as used herein, is intended to include a single medium as well as a collection of physically separate media, such as, for example, a collection of compact discs or one or more hard disk drives in combination with a computer memory. As used herein, a machine-readable storage medium does not include transitory forms of signal transmission.

[0093] Such software may also include information (e.g., data) carried as a data signal on a data carrier, such as a carrier wave. For example, machine-executable information may be included as a data-carrying signal embodied in a data carrier in which the signal encodes a sequence of instruction, or portion thereof, for execution by a machine (e.g., a computing device) and any related information (e.g., data structures and data) that causes the machine to perform any one of the methodologies and/or embodiments described herein.

[0094] Examples of a computing device include, but are not limited to, an electronic book reading device, a computer workstation, a terminal computer, a server computer, a handheld device (e.g., a tablet computer, a smartphone, etc.), a web appliance, a network router, a network switch, a network bridge, any machine capable of executing a sequence of instructions that specify an action to be taken by that machine, and any combinations thereof. In one example, a computing device may include and/or be included in a kiosk.

[0095] FIG. **6** shows a diagrammatic representation of one embodiment of a computing device in the exemplary form of a computer system **600** within which a set of instructions for causing a control system to perform any one or more of the aspects and/or methodologies of the present disclosure may be executed. It is also contemplated that multiple computing devices may be utilized to implement a specially configured set of instructions for causing one or more of the devices to perform any one or more of the aspects and/or methodologies of the present disclosure. Computer system **600** includes a processor **604** and a memory **608** that communicate with each other, and with other components, via a bus **612**. Bus **612** may include any of several types of bus structures including, but not limited to, a memory bus, a memory controller, a peripheral bus, a local bus, and any combinations thereof, using any of a variety of bus architectures.

[0096] Processor **604** may include any suitable processor, such as without limitation a processor incorporating logical circuitry for performing arithmetic and logical operations, such as an arithmetic and logic unit (ALU), which may be regulated with a state machine and directed by operational inputs from memory and/or sensors; processor **604** may be organized according to Von Neumann and/or Harvard architecture as a non-limiting example. Processor **604** may include, incorporate, and/or be incorporated in, without limitation, a microcontroller, microprocessor, digital signal processor (DSP), Field Programmable Gate Array (FPGA), Complex Programmable Logic Device (CPLD), Graphical Processing Unit (GPU), general purpose GPU, Tensor Processing Unit (TPU), analog or mixed signal processor, Trusted Platform Module (TPM), a floating point unit (FPU), and/or system on a chip (SoC).

[0097] Memory **608** may include various components (e.g., machine-readable media) including, but not limited to, a random-access memory component, a read only compo-

nent, and any combinations thereof. In one example, a basic input/output system **616** (BIOS), including basic routines that help to transfer information between elements within computer system **600**, such as during start-up, may be stored in memory **608**. Memory **608** may also include (e.g., stored on one or more machine-readable media) instructions (e.g., software) **620** embodying any one or more of the aspects and/or methodologies of the present disclosure. In another example, memory **608** may further include any number of program modules including, but not limited to, an operating system, one or more application programs, other program modules, program data, and any combinations thereof.

[0098] Computer system **600** may also include a storage device **624**. Examples of a storage device (e.g., storage device **624**) include, but are not limited to, a hard disk drive, a magnetic disk drive, an optical disc drive in combination with an optical medium, a solid-state memory device, and any combinations thereof. Storage device **624** may be connected to bus **612** by an appropriate interface (not shown). Example interfaces include, but are not limited to, SCSI, advanced technology attachment (ATA), serial ATA, universal serial bus (USB), IEEE 1394 (FIREWIRE), and any combinations thereof. In one example, storage device **624** (or one or more components thereof) may be removably interfaced with computer system **600** (e.g., via an external port connector (not shown)). Particularly, storage device **624** and an associated machine-readable medium **628** may provide nonvolatile and/or volatile storage of machine-readable instructions, data structures, program modules, and/or other data for computer system **600**. In one example, software **620** may reside, completely or partially, within machine-readable medium **628**. In another example, software **620** may reside, completely or partially, within processor **604**.

[0099] Computer system **600** may also include an input device **632**. In one example, a user of computer system **600** may enter commands and/or other information into computer system **600** via input device **632**. Examples of an input device **632** include, but are not limited to, an alpha-numeric input device (e.g., a keyboard), a pointing device, a joystick, a gamepad, an audio input device (e.g., a microphone, a voice response system, etc.), a cursor control device (e.g., a mouse), a touchpad, an optical scanner, a video capture device (e.g., a still camera, a video camera), a touchscreen, and any combinations thereof. Input device **632** may be interfaced to bus **612** via any of a variety of interfaces (not shown) including, but not limited to, a serial interface, a parallel interface, a game port, a USB interface, a FIREWIRE interface, a direct interface to bus **612**, and any combinations thereof. Input device **632** may include a touch screen interface that may be a part of or separate from display **636**, discussed further below. Input device **632** may be utilized as a user selection device for selecting one or more graphical representations in a graphical interface as described above.

[0100] A user may also input commands and/or other information to computer system **600** via storage device **624** (e.g., a removable disk drive, a flash drive, etc.) and/or network interface device **640**. A network interface device, such as network interface device **640**, may be utilized for connecting computer system **600** to one or more of a variety of networks, such as network **644**, and one or more remote devices **648** connected thereto. Examples of a network interface device include, but are not limited to, a network interface card (e.g., a mobile network interface card, a LAN card), a modem, and any combination thereof. Examples of a network include, but are not limited to, a wide area network (e.g., the Internet, an enterprise network), a local area network (e.g., a network associated with an office, a building, a campus or other relatively small geographic space), a telephone network, a data network associated with a telephone/voice provider (e.g., a mobile communications provider data and/or voice network), a direct connection between two computing devices, and any combinations thereof. A network, such as network **644**, may employ a wired and/or a wireless mode of communication. In general, any network topology may be used. Information (e.g., data, software **620**, etc.) may be communicated to and/or from computer system **600** via network interface device **640**.

[0101] Computer system **600** may further include a video display adapter **652** for communicating a displayable image to a display device, such as display device **636**. Examples of a display device include, but are not limited to, a liquid crystal display (LCD), a cathode ray tube (CRT), a plasma display, a light emitting diode (LED) display, and any combinations thereof. Display adapter **652** and display device **636** may be utilized in combination with processor **604** to provide graphical representations of aspects of the present disclosure. In addition to a display device, computer system **600** may include one or more other peripheral output devices including, but not limited to, an audio speaker, a printer, and any combinations thereof. Such peripheral output devices may be connected to bus **612** via a peripheral interface **656**. Examples of a peripheral interface include, but are not limited to, a serial port, a USB connection, a FIREWIRE connection, a parallel connection, and any combinations thereof.

[0102] The foregoing has been a detailed description of illustrative embodiments of the invention. Various modifications and additions can be made without departing from the spirit and scope of this invention. Features of each of the various embodiments described above may be combined with features of other described embodiments as appropriate in order to provide a multiplicity of feature combinations in associated new embodiments. Furthermore, while the foregoing describes a number of separate embodiments, what has been described herein is merely illustrative of the application of the principles of the present invention. Additionally, although particular methods herein may be illustrated and/or described as being performed in a specific order, the ordering is highly variable within ordinary skill to achieve systems and methods according to the present disclosure. Accordingly, this description is meant to be taken only by way of example, and not to otherwise limit the scope of this invention.

[0103] Exemplary embodiments have been disclosed above and illustrated in the accompanying drawings. It will be understood by those skilled in the art that various changes, omissions and additions may be made to that which is specifically disclosed herein without departing from the spirit and scope of the present invention.

What is claimed is:

1. An electric aircraft configured to implement a layered data network, wherein the electric aircraft comprises:

a plurality of communication components configured to facilitate communication with a plurality of parties, wherein the plurality of communication components comprises:

a first communication component configured to facilitate radio communication through a first layer of the layered data network at a first bandwidth; and

a second communication component configured to facilitate mobile network communication through a second layer of the layered data network at a second bandwidth.

2. The electric aircraft of claim **1**, wherein the first communication component comprises an antenna configured to provide radio communication between the electric aircraft and a first party of the plurality of parties.

3. The electric aircraft of claim **1**, wherein the second communication component comprises a mobile communication equipment configured to communicate with a second party of the plurality of parties.

4. The electric aircraft of claim **1**, wherein the plurality of communication components further comprises a third communication component, wherein the third communication component is configured to facilitate satellite communication with a third party of the plurality of parties through a third layer of the layered data network at a third bandwidth.

5. The electric aircraft of claim **1**, wherein the electric aircraft comprises an electric propulsor configured to generate thrust.

6. The electric aircraft of claim **1**, wherein the electric aircraft further comprise a flight controller in communication with the plurality of communication components.

7. The electric aircraft of claim **1**, wherein one or more of the first communication component and the second communication component is configured to communicate a flight element using the layered data network.

8. The electric aircraft of claim **1**, wherein the electric aircraft is configured to implement a failover mechanism.

9. The electric aircraft of claim **1**, wherein the first bandwidth is greater than the second bandwidth and the third bandwidth.

10. The electric aircraft of claim **1**, wherein the second communication component is configured to provide mobile network communication in the form of at least one of a 4G communication and a 5G communication.

11. A method to implement a layered data network in electric aircraft, the method comprising:

facilitating, by a first communication component of a plurality of communication components, communication through a first layer at a first bandwidth; and

facilitating, by a second communication component of the plurality of communication components, communication through a second layer at a second bandwidth.

12. The method of claim **11**, wherein the method further comprises providing, by an antenna of the first communication component, radio communication between the electric aircraft and a first party of the plurality of parties.

13. The method of claim **11**, wherein the method further comprises communicating, by a mobile communication equipment of the second communication component, with a second party of the plurality of parties.

14. The method of claim **11**, wherein the method further comprises facilitating, by a third communication component of the plurality of communication components, satellite communication with a third party of the plurality of parties through a third layer of the layered data network at a third bandwidth.

15. The method of claim **11**, wherein method further comprises generating thrust as a function of the electric aircraft.

16. The method of claim **11**, wherein the electric aircraft further comprise a flight controller in communication with the plurality of communication components.

17. The method of claim **11**, wherein the method further comprises communicating, by one or more of the first communication component and the second communication component, a flight element using the layered data network.

18. The method of claim **11**, wherein the method further comprises implementing a failover mechanism.

19. The method of claim **11**, wherein the first bandwidth is greater than the second bandwidth and the third bandwidth.

20. The method of claim **11**, wherein the method further comprises providing, by the second communication component, mobile network communication in the form of at least one of a 4G communication and a 5G communication.

* * * * *